

Material Safety Data Sheet

Fast 50

Contract Grade Multi Purpose Adhesive

SECTION I - PRODUCT IDENTIFICATION

Generic ID: **Latex Based Flooring Adhesive**
DOT Hazard Classification: **None**
Product Identity: **JRC #100 Plus Multi Purpose Adhesive**

SECTION II - HAZARDOUS COMPONENTS

None per OSHA Regulation: 29CFR1910.1200
None per SARA Title III, Section 313 and TSCA 40 CFR 372

SECTION III - PHYSICAL DATA

Initial Boiling Point:	212°F
Vapor Pressure:	Same as water
Vapor Density (Air = 1.0):	Same as water
Specific Gravity:	1.15
G/L VOC (calculated)	0.00
Percent Volatiles:	32.0%

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point:	NA
Explosive Limit (Product):	NA
Extinguishing Media:	None to avoid
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, oxides of nitrogen and sulfur
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus.
Unusual Fire & Explosion Hazards:	None

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level:	NA
Threshold Limit Value:	NA

Effects Of Exposure: Eyes: Possible mild irritation. Skin: Possible mild irritation. Breathing: None known. Swallowing: Can cause G.I. blockage.

First Aid: Skin: Soap and water. Eyes: Flush with water, lifting upper and lower lids occasionally. Ingestion: Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation: If affected, remove individual to fresh air. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Stability:	Stable
Incompatibility:	None
Hazardous Decomposition:	None
Hazardous Polymerization:	None
Conditions To Avoid:	None Known

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations. Check all local, state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and entrances to insure good ventilation. Respirator Protection: None needed. Protective Gloves: If sensitive. Eye Protection: Wear glasses or protective goggles to avoid splashes. Other Protective Equipment: None required. Wash Hands Thoroughly with Soap and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and window should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with company or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.

KEEP OUT OF REACH OF CHILDREN



Capitol Adhesives, Inc.
PO Box 2023
300 Cross Plains Blvd.
Dalton, Georgia 30720

800 831 8381 • 706 277 6241 • fax 706 277 5753